




Mobile access steps with platform, single-sided access, with aluminium treads and platform - 41971

Can be released safely and quickly for flexibility while working: comfortable ascent, four sprung castors for stability and easy handling.



Product description

- Can be released safely and quickly for flexibility while working: comfortable ascent, four sprung castors for stability and easy handling.
- Quick and easy assembly thanks to the new connecting elements.
- Mobile and quick to set up with four sprung swivel castors (two of which have brakes).
- Maximum safety through platform guardrail at a height of 1.00 m on three sides.
- Comfortable ascent thanks to 200 mm deep treads.
- Large platform, 600 x 800 mm.
- Maximum load 150 kg.



Hints and special features

Optional double-sided handrail in compliance with DIN EN 131-7 on the steps.

Complies with EN 131-7

Product features



Base 0,77 m × 1,27 m	Coating natural	Connection between stiles and rungs/stiles welded	Guardrail height 1000 mm	Load capacity max. 150 kg
Material aluminium	Number of rungs, incl. platform 3	Platform height 0.72 m	Platform length 800 mm	Platform width 600 mm
Standards EN 131-7	Transport dimensions 1.180 mm × 820 mm × 330 mm	Tread depth 200 mm	Type of rungs/treads serrated	Vertical distance between each rung/ tread 240 mm
Warranty 10 years	Weight 28.5 kg	Working height 2.7 m		