



# Mobile access steps with platform, single-sided access, with aluminium treads and platform - 41973

Can be released safely and quickly for flexibility while working: comfortable ascent, four sprung castors for stability and easy handling.



## Product description

- Can be released safely and quickly for flexibility while working: comfortable ascent, four sprung castors for stability and easy handling.
- Quick and easy assembly thanks to the new connecting elements.
- Mobile and quick to set up with four sprung swivel castors (two of which have brakes).
- Maximum safety through platform guardrail at a height of 1.00 m on three sides.
- Comfortable ascent thanks to 200 mm deep treads.
- Large platform, 600 x 800 mm.
- Maximum load 150 kg.



## Hints and special features

Optional double-sided handrail in compliance with DIN EN 131-7 on the steps.

Complies with EN 131-7



**ZARGES**

More information about the product, accessories and spare parts:  
<https://www.zarges.com/uk/products/mobile-access-steps-with-platform-single-sided-access-with-aluminium-treads-and-platform-41973>



## Product features

|                                |   |   |   |  |
|--------------------------------|---|---|---|--|
| Base<br><b>0,87 m × 1,63 m</b> | Coating<br><b>natural</b>                                 | Connection between stiles and rungs/stiles<br><b>welded</b> | Guardrail height<br><b>1000 mm</b>      | Load capacity<br><b>max. 150 kg</b>                        |
| Material<br><b>aluminium</b>   | Number of rungs, incl. platform<br><b>5</b>               | Platform height<br><b>1.2 m</b>                             | Platform length<br><b>800 mm</b>        | Platform width<br><b>600 mm</b>                            |
| Standards<br><b>EN 131-7</b>   | Transport dimensions<br><b>1.380 mm × 950 mm × 420 mm</b> | Tread depth<br><b>200 mm</b>                                | Type of rungs/treads<br><b>serrated</b> | Vertical distance between each rung/tread<br><b>240 mm</b> |
| Warranty<br><b>10 years</b>    | Weight<br><b>35 kg</b>                                    | Working height<br><b>3.2 m</b>                              |   |  |