




Mobile access steps with platform, single-sided access, with light-alloy treads and platform - 41974

Can be released safely and quickly for flexibility while working: comfortable ascent, four sprung castors for stability and easy handling.

Product description

- Can be released safely and quickly for flexibility while working: comfortable ascent, four sprung castors for stability and easy handling.
- Quick and easy assembly thanks to the new connecting elements.
- Mobile and ready for operation in no time with four sprung swivel castors (two of each with brakes).
- Maximum safety through platform railing at a height of 1.00 m on three sides.
- Comfortable ascent through treads with a depth of 200 mm.
- Spacious platform, 600 x 800 mm.
- Maximum loading capacity 150 kg.



Hints and special features

Double-sided handrail in accordance with EN 131-7 on access optional.

Complies with EN 131-7

Product features

| | | | | |
|--------------------------------|---------------------------|--|------------------------------------|-------------------------------------|
| Base 0,93 m × 1,81 m | Coating natural | Connection Stile-Rung welded | Guardrail height 1000 mm | Load capacity max. 150 kg |
| Material | Number of rungs, incl. | Pitch rung/tread | Platform height | Platform length |



| | | | | |
|---------------------------------|------------------------------|---|------------------------------|------------------------------------|
| Aluminium | platform 6 | 240 mm | 1.44 m | 800 mm |
| Platform width 600 mm | Standards EN 131-7 | Transport dimensions 1.850 mm × 1.000 mm × 330 mm | Tread depth 200 mm | Type rung/tread serrated |
| Warranty 10 years | Weight 38.4 kg | Working height 3.45 m | | |