




Mobile access steps with platform, single-sided access, with aluminium treads and platform - 41975

Can be released safely and quickly for flexibility while working: comfortable ascent, four sprung castors for stability and easy handling.



Product description

- Can be released safely and quickly for flexibility while working: comfortable ascent, four sprung castors for stability and easy handling.
- Quick and easy assembly thanks to the new connecting elements.
- Mobile and quick to set up with four sprung swivel castors (two of which have brakes).
- Maximum safety through platform guardrail at a height of 1.00 m on three sides.
- Comfortable ascent thanks to 200 mm deep treads.
- Large platform, 600 x 800 mm.
- Maximum load 150 kg.



Hints and special features

Optional double-sided handrail in compliance with DIN EN 131-7 on the steps.

Complies with EN 131-7



Product features

| | | | | |
|--------------------------------|---|--|---|---|
| Base 0,98 m × 1,99 m | Coating natural | Connection between stiles and rungs/stiles welded | Guardrail height 1000 mm | Load capacity max. 150 kg |
| Material aluminium | Number of rungs, incl. platform 7 | Platform height 1.68 m | Platform length 800 mm | Platform width 600 mm |
| Standards EN 131-7 | Transport dimensions 1.920 mm × 1.060 mm × 410 mm | Tread depth 200 mm | Type of rungs/treads serrated | Vertical distance between each rung/ tread 240 mm |
| Warranty 10 years | Weight 41.8 kg | Working height 3.7 m | | |