



Mobile access steps with platform, single-sided access, with aluminium treads and platform - 41975

Can be released safely and quickly for flexibility while working: comfortable ascent, four sprung castors for stability and easy handling.



Product description

- Can be released safely and quickly for flexibility while working: comfortable ascent, four sprung castors for stability and easy handling.
- Quick and easy assembly thanks to the new connecting elements.
- Mobile and quick to set up with four sprung swivel castors (two of which have brakes).
- Maximum safety through platform guardrail at a height of 1.00 m on three sides.
- Comfortable ascent thanks to 200 mm deep treads.
- Large platform, 600 x 800 mm.
- Maximum load 150 kg.



Hints and special features

Optional double-sided handrail in compliance with DIN EN 131-7 on the steps.

Complies with EN 131-7



Product features

Base	0,98 m × 1,99 m
Coating	natural
Connection between stiles and rungs/stiles	welded
Guardrail height	1000 mm
Load capacity	max. 150 kg
Material	aluminium
Number of rungs, incl. platform	7
Platform height	1.68 m
Platform length	800 mm
Platform width	600 mm
Standards	EN 131-7
Transport dimensions	1.920 mm × 1.060 mm × 410 mm
Tread depth	200 mm
Type of rungs/treads	serrated
Vertical distance between each rung/tread	240 mm
Warranty	10 years
Weight	41.8 kg
Working height	3.7 m

ZARGES (U.K.) Ltd.

8 Holdom Avenue. Saxon Park Ind. Est.

Bletchley MK1 1QU

Tel: 01908 641118

Fax:

sales@zarges.co.uk

www.zarges.com/uk

Effective 3/5/2026

Subject to change or error.