



Mobile access steps with platform, double-sided access, with light-alloy treads and platform - 41983

Maximum flexibility while ascending and descending, larger working area on the treads and four sprung castors for a high degree of mobility and stability.

Product description

- Maximum flexibility while ascending and descending, larger working area on the treads and four sprung castors for a high degree of mobility and stability.
- Quick and easy assembly thanks to the new connecting elements.
- Mobile and ready for operation in no time with four sprung swivel castors (two of each with brakes).
- Maximum safety through double-sided platform railing at a height of 1.00 m.
- Comfortable ascent through treads with a depth of 200 mm.
- Spacious platform, 600 x 800 mm.
- Maximum loading capacity 150 kg.



Hints and special features

Double-sided handrail in accordance with EN 131-7 on access optional.

Complies with EN 131-7

Product features

Base 0,87 m × 2,06 m	Coating natural	Connection Stile-Rung welded	Guardrail height 1000 mm	Load capacity max. 150 kg
Material	Number of rungs, incl.	Number of treads	Pitch rung/tread	Platform height



Aluminium	platform 2 x 5	5	240 mm	1.2 m
Platform length 800 mm	Platform width 600 mm	Standards EN 131-7	Transport dimensions 1.850 mm x 940 mm x 440 mm	Tread depth 200 mm
Type rung/tread serrated	Warranty 10 years	Weight 41 kg	Working height 3.2 m	