



# Mobile access steps with platform, double-sided access, with aluminium treads and platform - 41985

Maximum flexibility while ascending and descending, larger working area on the treads and four sprung castors for a high degree of mobility and stability.



## Product description

- Maximum flexibility while ascending and descending, larger working area on the treads and four sprung castors for a high degree of mobility and stability.
- Quick and easy assembly thanks to the new connecting elements.
- Mobile and quick to set up with four sprung swivel castors (two of which have brakes).
- Maximum safety through double-sided platform guardrail at a height of 1.00 m.
- Comfortable ascent thanks to 200 mm deep treads.
- Large platform, 600 x 800 mm.
- Maximum load 150 kg.



## Hints and special features

Optional double-sided handrail in compliance with DIN EN 131-7 on the steps.

Complies with EN 131-7



## Product features

Base	0,98 m × 2,62 m
Coating	natural
Connection between stiles and rungs/stiles	welded
Guardrail height	1000 mm
Load capacity	max. 150 kg
Material	aluminium
Number of rungs, incl. platform	2 × 7
Number of treads	7
Platform height	1.68 m
Platform length	800 mm
Platform width	600 mm
Standards	EN 131-7
Transport dimensions	2.250 mm × 1.060 mm × 410 mm
Tread depth	200 mm
Type of rungs/treads	serrated
Vertical distance between each rung/tread	240 mm
Warranty	10 years
Weight	51.7 kg
Working height	3.7 m



More information about the product, accessories and spare parts:  
<https://www.zarges.com/uk/products/mobile-access-steps-with-platform-double-sided-access-with-aluminium-treads-and-platform-41985>



ZARGES (U.K.) Ltd.

Blackwater Trading Estate, The Causeway  
CM9 4LJ Maldon, Essex

Tel: 01908 641118

Fax:  
[sales@zarges.co.uk](mailto:sales@zarges.co.uk)

[www.zarges.com/uk](http://www.zarges.com/uk)

Effective 4/6/2026  
Subject to change or error.