



Mobile access steps with platform, double-sided access, with aluminium treads and platform - 41985

Maximum flexibility while ascending and descending, larger working area on the treads and four sprung castors for a high degree of mobility and stability.



Product description

- Maximum flexibility while ascending and descending, larger working area on the treads and four sprung castors for a high degree of mobility and stability.
- Quick and easy assembly thanks to the new connecting elements.
- Mobile and quick to set up with four sprung swivel castors (two of which have brakes).
- Maximum safety through double-sided platform guardrail at a height of 1.00 m.
- Comfortable ascent thanks to 200 mm deep treads.
- Large platform, 600 x 800 mm.
- Maximum load 150 kg.



Hints and special features

Optional double-sided handrail in compliance with DIN EN 131-7 on the steps.



Complies with EN 131-7

Product features

Base 0,98 m × 2,62 m	Coating natural	Connection between stiles and rungs/stiles welded	Guardrail height 1000 mm	Load capacity max. 150 kg
Material aluminium	Number of rungs, incl. platform 2 × 7	Number of treads 7	Platform height 1.68 m	Platform length 800 mm
Platform width 600 mm	Standards EN 131-7	Transport dimensions 2.250 mm × 1.060 mm × 410 mm	Tread depth 200 mm	Type of rungs/treads serrated
Vertical distance between each rung/tread 240 mm	Warranty 10 years	Weight 51.7 kg	Working height 3.7 m	