



## Nova S - 42453

The classic model for safe standing and comfortable working, with a practical storage tray and high-stability patented rung-stile connection.

### Product description

- The classic model for safe standing and comfortable working, with a practical storage tray and high-stability patented rung-stile connection.
- Large standing platform with anti-slip serrated surface.
- Practical storage tray with plenty of space for tools and small parts.
- 80 mm deep surfaces to stand on.
- Stable tread construction: robust, durable, flanged rung-stile connection.
- Optimal platform stability thanks to extruded aluminium sections.
- Two plastic locating guides lock steps together when it's closed.
- Stability through slip-resistant plastic end caps.
- Enclosed rung profile and integrated guide tube.



### Hints and special features

Complies with EN 131 Professional.

### Product features

Base	Coating	Connection between stiles and rungs/stiles	Load capacity	Material
------	---------	--	---------------	----------



<b>0,69 m × 0,42 m</b>	<b>natural</b>	<b>flanged</b>	<b>max. 150 kg</b>	<b>aluminium</b>
Number of rungs, incl. platform <b>3</b>	Overall base width <b>0.42 m</b>	Overall length <b>1.34 m</b>	Platform height <b>0.61 m</b>	Platform length <b>250 mm</b>
Platform width <b>250 mm</b>	Standards <b>EN 131 professional</b>	Stile depth <b>48 mm</b>	Stile depth <b>48 mm</b>	Stile depth steps/back stay <b>48mm / 48mm</b>
Storage tray <b>Plastic</b>	Transport dimensions <b>1.350 mm × 420 mm × 120 mm</b>	Tread depth <b>80 mm</b>	Type of rungs/treads <b>serrated</b>	Vertical distance between each rung/tread <b>216 mm</b>
Vertical ladder height <b>1.22 m</b>	Warranty <b>10 years</b>	Weight <b>4.8 kg</b>	Working height <b>2.6 m</b>	certification-mark-pf <b>TÜV-SÜD</b>