



Nova S - 42455

The classic model for safe standing and comfortable working, with a practical storage tray and high-stability patented rung-stile connection.

Product description

- The classic model for safe standing and comfortable working, with a practical storage tray and high-stability patented rung-stile connection.
- Large standing platform with anti-slip serrated surface.
- Practical storage tray with plenty of space for tools and small parts.
- 80 mm deep surfaces to stand on.
- Stable tread construction: robust, durable, flanged rung-stile connection.
- Optimal platform stability thanks to extruded aluminium sections.
- Two plastic locating guides lock steps together when it's closed.
- Stability through slip-resistant plastic end caps.
- Enclosed rung profile and integrated guide tube.



Hints and special features

Complies with EN 131 Professional.

Product features

Base	Coating	Connection between stiles and rungs/stiles	Load capacity	Material
------	---------	--	---------------	----------



0,99 m × 0,46 m	natural	flanged	max. 150 kg	aluminium
Number of rungs, incl. platform 5	Overall base width 0.46 m	Overall length 1.8 m	Platform height 1.05 m	Platform length 250 mm
Platform width 250 mm	Standards EN 131 professional	Stile depth 48 mm	Stile depth 48 mm	Stile depth steps/back stay 48mm / 48mm
Storage tray Plastic	Transport dimensions 1.810 mm × 470 mm × 120 mm	Tread depth 80 mm	Type of rungs/treads serrated	Vertical distance between each rung/tread 216 mm
Vertical ladder height 1.65 m	Warranty 10 years	Weight 6.9 kg	Working height 3.05 m	