



# Nova S - 42457

The classic model for safe standing and comfortable working, with a practical storage tray and high-stability patented rung-stile connection.

## Product description

- The classic model for safe standing and comfortable working, with a practical storage tray and high-stability patented rung-stile connection.
- Large platform with anti-slip ribbing.
- Practical tray with plenty of space for tools and small items.
- 80 mm deep surfaces to stand on.
- High-strength perlon belts prevent splay.
- Patented tread construction: robust, stable, durable, flanged rung-stile connection.
- The extruded aluminium sections give the platform optimum stability.
- Two extruded section bridge raisers.
- Firm positioning thanks to anti-slip plastic end caps.
- Enclosed rung profile and integrated guide tube.



## Hints and special features

Complies with EN 131 Professional.

## Product features

Anti splay <b>Belt strap</b>	Base <b>1,28 m x 0,51 m</b>	Coating <b>natural</b>	Connection Stile-Rung <b>flanged</b>	Load capacity <b>max. 150 kg</b>
Material <b>Aluminium</b>	Number of rungs, incl. platform <b>7</b>	Overall base width <b>0.51 m</b>	Overall length <b>2.26 m</b>	Pitch rung/tread <b>216 mm</b>
Platform height <b>1.48 m</b>	Platform length <b>250 mm</b>	Platform width <b>250 mm</b>	Standards <b>EN 131 professional</b>	Stile depth <b>48 mm</b>



Stile depth <b>48 mm</b>	Stile depth steps/back stay <b>48mm / 48mm</b>	Transport dimensions <b>2.270 mm × 520 mm × 120 mm</b>	Tray <b>Plastic</b>	Tread depth <b>80 mm</b>
Type rung/tread <b>serrated</b>	Vertical ladder height <b>2.08 m</b>	Warranty <b>10 years</b>	Weight <b>9.1 kg</b>	Working height <b>3.5 m</b>