



## Nova S - 42460

The classic model for safe standing and comfortable working, with a practical storage tray and high-stability patented rung-stile connection.

### Product description

- The classic model for safe standing and comfortable working, with a practical storage tray and high-stability patented rung-stile connection.
- Large standing platform with anti-slip serrated surface.
- Practical storage tray with plenty of space for tools and small parts.
- 80 mm deep surfaces to stand on.
- High-strength Perlon belts with sewn-in fixing straps prevent splay, from 7 rungs.
- Stable tread construction: robust, durable, flanged rung-stile connection.
- Optimal platform stability thanks to extruded aluminium sections.
- Two plastic locating guides lock steps together when it's closed.
- Stability through slip-resistant plastic end caps.
- Enclosed rung profile and integrated guide tube.



### Hints and special features

Complies with EN 131 Professional.

### Product features



Anti-splay mechanism <b>Belt strap</b>	Base <b>1,76 m × 0,58 m</b>	Coating <b>natural</b>	Connection between stiles and rungs/stiles <b>flanged</b>	Load capacity <b>max. 150 kg</b>
Material <b>aluminium</b>	Number of rungs, incl. platform <b>10</b>	Overall base width <b>0.58 m</b>	Overall length <b>2.95 m</b>	Platform height <b>2.13 m</b>
Platform length <b>250 mm</b>	Platform width <b>250 mm</b>	Standards <b>EN 131 professional</b>	Stile depth <b>48 mm</b>	Stile depth <b>48 mm</b>
Stile depth steps/back stay <b>48mm / 48mm</b>	Storage tray <b>Plastic</b>	Transport dimensions <b>2.960 mm × 590 mm × 120 mm</b>	Tread depth <b>80 mm</b>	Type of rungs/treads <b>serrated</b>
Vertical distance between each rung/ tread <b>216 mm</b>	Vertical ladder height <b>2.73 m</b>	Warranty <b>10 years</b>	Weight <b>12.4 kg</b>	Working height <b>4.15 m</b>
certification-mark-pf <b>TÜV-SÜD</b>				