



Nova S - 42460

The classic model for safe standing and comfortable working, with a practical storage tray and high-stability patented rung-stile connection.

Product description

- The classic model for safe standing and comfortable working, with a practical storage tray and high-stability patented rung-stile connection.
- Large standing platform with anti-slip serrated surface.
- Practical storage tray with plenty of space for tools and small parts.
- 80 mm deep surfaces to stand on.
- High-strength Perlon belts with sewn-in fixing straps prevent splay, from 7 rungs.
- Stable tread construction: robust, durable, flanged rung-stile connection.
- Optimal platform stability thanks to extruded aluminium sections.
- Two plastic locating guides lock steps together when it's closed.
- Stability through slip-resistant plastic end caps.
- Enclosed rung profile and integrated guide tube.



Hints and special features

Complies with EN 131 Professional.

Product features



| | | | | |
|---|---|---|---|---|
| Anti-splay mechanism Belt strap | Base 1,76 m × 0,58 m | Coating natural | Connection between stiles and rungs/stiles flanged | Load capacity max. 150 kg |
| Material aluminium | Number of rungs, incl. platform 10 | Overall base width 0.58 m | Overall length 2.95 m | Platform height 2.13 m |
| Platform length 250 mm | Platform width 250 mm | Standards EN 131 professional | Stile depth 48 mm | Stile depth 48 mm |
| Stile depth steps/back stay 48mm / 48mm | Storage tray Plastic | Transport dimensions 2.960 mm × 590 mm × 120 mm | Tread depth 80 mm | Type of rungs/treads serrated |
| Vertical distance between each rung/ tread 216 mm | Vertical ladder height 2.73 m | Warranty 10 years | Weight 12.4 kg | Working height 4.15 m |