



## Everest 2DE - 44820

Safe, flexible and suitable for great heights, with an excellent price/performance ratio.

### Product description

- Safe, flexible and suitable for great heights, with an excellent price/performance ratio.
- Convenient and precise rung-by-rung height adjustment in increments of 280 mm.
- Both parts of the ladder can also be used separately as single ladders for Order Nos. 44834 and 44820
- Sturdy triangular rungs made from extruded profiles that have a horizontal stepping surface when in the use position.
- Both parts of the ladder can also be used separately as single ladders.
- Outside width of lower ladder: 420 mm.
- Positive guide fittings of aluminium extruded section.
- Replaceable 2-component plastic end caps ensure positioning without risk of slipping.



### Hints and special features

Complies with EN 131 Professional.

### Product features

Certification	TÜV-SÜD
Coating	natural



Connection between stiles and rungs/stiles	flanged
External width of lower ladder	420 mm
Load capacity	max. 150 kg
Material	aluminium
Number of rungs	10
Number of rungs	2 × 10
Overall length, extended	4.93 m
Overall length, retracted	2.98 m
Standards	EN 131 professional
Stile depth	68 mm
Transport dimensions	2.980 mm × 430 mm × 120 mm
Tread depth	38 mm
Type of rungs/treads	serrated
Vertical distance between each rung/tread	265 mm
Warranty	10 years
Weight	11.3 kg
Wide crosspiece	0.9 m
Working height	5.65 m

ZARGES (U.K.) Ltd.

8 Holdom Avenue. Saxon Park Ind. Est.  
 Bletchley MK1 1QU

Tel: 01908 641118

Fax:  
 sales@zarges.co.uk

[www.zarges.com/uk](http://www.zarges.com/uk)

Effective 18/5/2026  
 Subject to change or error.