



## Everest 2DE - 44820

Safe, flexible and suitable for great heights, with an excellent price/performance ratio.

### Product description

- Safe, flexible and suitable for great heights, with an excellent price/performance ratio.
- Convenient and precise rung-by-rung height adjustment in increments of 280 mm.
- Both parts of the ladder can also be used separately as single ladders for Order Nos. 44834 and 44820
- Sturdy triangular rungs made from extruded profiles that have a horizontal stepping surface when in the use position.
- Both parts of the ladder can also be used separately as single ladders.
- Outside width of lower ladder: 420 mm.
- Positive guide fittings of aluminium extruded section.
- Replaceable 2-component plastic end caps ensure positioning without risk of slipping.



### Hints and special features

Complies with EN 131 Professional.

### Product features

Coating	Connection between stiles and rungs/stiles	External width of lower ladder	Load capacity	Material
---------	--	--------------------------------	---------------	----------



<b>natural</b>	<b>flanged</b>	<b>420 mm</b>	<b>max. 150 kg</b>	<b>aluminium</b>
Number of rungs <b>10</b>	Number of rungs <b>2 × 10</b>	Overall length, extended <b>4.93 m</b>	Overall length, retracted <b>2.98 m</b>	Standards <b>EN 131 professional</b>
Stile depth <b>68 mm</b>	Transport dimensions <b>2.980 mm × 430 mm × 120 mm</b>	Tread depth <b>38 mm</b>	Type of rungs/treads <b>serrated</b>	Vertical distance between each rung/tread <b>265 mm</b>
Warranty <b>10 years</b>	Weight <b>11.3 kg</b>	Wide crosspiece <b>0.9 m</b>	Working height <b>5.65 m</b>	certification-mark-pf <b>TÜV-SÜD</b>