



Everest 2DE - 44824

Safe, flexible and suitable for great heights, with an excellent price/performance ratio.

Product description

- Safe, flexible and suitable for great heights, with an excellent price/performance ratio.
- Convenient and precise rung-by-rung height adjustment in increments of 280 mm.
- Both parts of the ladder can also be used separately as single ladders for Order Nos. 44834 and 44820
- Sturdy triangular rungs made from extruded profiles that have a horizontal stepping surface when in the use position.
- Outside width of lower ladder: 420 mm.
- Positive guide fittings of aluminium extruded section.
- Replaceable 2-component plastic end caps ensure positioning without risk of slipping.



Hints and special features

Complies with EN 131 Professional.

Product features

Coating natural	Connection between stiles and rungs/stiles flanged	External width of lower ladder 420 mm	Load capacity max. 150 kg	Material aluminium



Number of rungs 14	Number of rungs 2 × 14	Overall length, extended 7.17 m	Overall length, retracted 4.1 m	Standards EN 131 professional
Stile depth 85 mm	Transport dimensions 4.100 mm × 430 mm × 135 mm	Tread depth 38 mm	Type of rungs/treads serrated	Vertical distance between each rung/tread 265 mm
Warranty 10 years	Weight 17.8 kg	Wide crosspiece 1.1 m	Working height 7.85 m	certification-mark-pf TÜV-SÜD