



Everest 2DE - 44824

Safe, flexible and suitable for great heights, with an excellent price/performance ratio.

Product description

- Safe, flexible and suitable for great heights, with an excellent price/performance ratio.
- Convenient and precise rung-by-rung height adjustment in increments of 280 mm.
- Both parts of the ladder can also be used separately as single ladders for Order Nos. 44834 and 44820
- Sturdy triangular rungs made from extruded profiles that have a horizontal stepping surface when in the use position.
- Outside width of lower ladder: 420 mm.
- Positive guide fittings of aluminium extruded section.
- Replaceable 2-component plastic end caps ensure positioning without risk of slipping.



Hints and special features

Complies with EN 131 Professional.

Product features

Certification	TÜV-SÜD
Coating	natural
Connection between stiles and rungs/stiles	flanged
External width of lower ladder	420 mm



Load capacity	max. 150 kg
Material	aluminium
Number of rungs	14
Number of rungs	2 × 14
Overall length, extended	7.17 m
Overall length, retracted	4.1 m
Standards	EN 131 professional
Stile depth	85 mm
Transport dimensions	4.100 mm × 430 mm × 135 mm
Tread depth	38 mm
Type of rungs/treads	serrated
Vertical distance between each rung/tread	265 mm
Warranty	10 years
Weight	17.8 kg
Wide crosspiece	1.1 m
Working height	7.85 m

ZARGES (U.K.) Ltd.

8 Holdom Avenue, Saxon Park Ind. Est.
 Bletchley MK1 1QU

Tel: 01908 641118

Fax:
sales@zarges.co.uk

www.zarges.com/uk

Effective 18/5/2026
 Subject to change or error.