



Everest 2DE - 44834

Safe, flexible and suitable for great heights, with an excellent price/performance ratio.

Product description

- Safe, flexible and suitable for great heights, with an excellent price/performance ratio.
- Convenient and precise rung-by-rung height adjustment in increments of 280 mm.
- Both parts of the ladder can also be used separately as single ladders for Order Nos. 44834 and 44820
- Sturdy triangular rungs made from extruded profiles that have a horizontal stepping surface when in the use position.
- Both parts of the ladder can also be used separately as single ladders.
- Outside width of lower ladder: 420 mm.
- Positive guide fittings of aluminium extruded section.
- Replaceable 2-component plastic end caps ensure positioning without risk of slipping.



Hints and special features

Complies with EN 131 Professional.

Product features

Coating	Connection between stiles and rungs/stiles	External width of lower ladder	Load capacity	Material
---------	--	--------------------------------	---------------	----------



natural	flanged	420 mm	max. 150 kg	aluminium
Number of rungs 8	Number of rungs 2 × 8	Overall length, extended 3.8 m	Overall length, retracted 2.42 m	Standards EN 131 professional
Stile depth 58 mm	Transport dimensions 2.420 mm × 420 mm × 115 mm	Tread depth 38 mm	Type of rungs/treads serrated	Vertical distance between each rung/tread 265 mm
Warranty 10 years	Weight 9.3 kg	Wide crosspiece 0.8 m	Working height 4.6 m	certification-mark-pf TÜV-SÜD