



## Skymaster DX - 44837

Probably the only ladder you'll ever need! Our best selling ladder offers unrivalled flexibility and durability.

### Product description

- Probably the only ladder you'll ever need! Our best selling ladder offers unrivalled flexibility and durability.
- Upper ladder can also be used separately as single ladders for Order Nos. 44837-44840.
- Sturdy triangular rungs made from extruded profiles that have a horizontal stepping surface when in the use position.
- Upper ladder can also be used separately as single ladders.
- High-strength Perlon straps with sewn-in fixing tab to prevent splaying.
- Stiles made from extruded aluminium sections for maximum stability.
- Replaceable 2-component plastic end caps ensure positioning without risk of slipping.
- High strength, non-twist rung/stile connections.
- Cannot be used on stairs.



### Hints and special features

Complies with EN 131 Professional.

### Product features



Coating <b>natural</b>	Connection between stiles and rungs/stiles <b>flanged</b>	Ladder length as 3-part single ladder <b>4.4 m</b>	Length as 2-part single ladder and as stepladder with push- on section <b>3.25 m</b>	Load capacity <b>max. 150 kg</b>
Material <b>aluminium</b>	Number of rungs <b>7</b>	Number of rungs <b>3 × 7</b>	Overall length, retracted <b>2.14 m</b>	Standards <b>EN 131 professional</b>
Stile depth <b>58 mm</b>	Transport dimensions <b>2.130 mm × 500 mm × 170 mm</b>	Tread depth <b>38 mm</b>	Type of rungs/treads <b>serrated</b>	Vertical distance between each rung/ tread <b>265 mm</b>
Warranty <b>10 years</b>	Weight <b>13.8 kg</b>	Wide crosspiece <b>0.8 m</b>	Working height as 3- part single ladder <b>5.2 m</b>	certification-mark-pf <b>TÜV-SÜD</b>