



Skymaster DX - 44837

Functionality and flexibility with standard features and excellent price/performance.

Product description

- Functionality and flexibility with standard features and excellent price/performance.
- Upper ladder can also be used separately as single ladders for Order Nos. 44837-44840.
- Sturdy triangular rungs made from extruded profiles that have a horizontal stepping surface when in the use position.
- Upper ladder can also be used separately as single ladders.
- Anti-spread protection provided by high-strength polyester webbing with a sewn-in attachment tab.
- Stiles made from extruded aluminium sections for maximum stability.
- Replaceable 2-component plastic end caps ensure positioning without risk of slipping.
- High strength, non-twist rung/stile connections.
- Cannot be used on stairs.



Hints and special features

Complies with EN 131 Professional.

Product features

Certification	TÜV-SÜD
Coating	natural



Connection between stiles and rungs/stiles	flanged
Ladder length as 3-part single ladder	4.4 m
Length as 2-part single ladder and as stepladder with push-on section	3.25 m
Load capacity	max. 150 kg
Material	aluminium
Number of rungs	7
Number of rungs	3 × 7
Overall length, retracted	2.14 m
Standards	EN 131 professional
Stile depth	58 mm
Transport dimensions	2.130 mm × 500 mm × 170 mm
Tread depth	38 mm
Type of rungs/treads	serrated
Vertical distance between each rung/tread	265 mm
Warranty	10 years
Weight	13.8 kg
Wide crosspiece	0.8 m
Working height as 3-part single ladder	5.2 m

ZARGES (U.K.) Ltd.

Blackwater Trading Estate, The Causeway
 CM9 4LJ Maldon, Essex

Tel: 01908 641118

Fax:
sales@zarges.co.uk

www.zarges.com/uk

Effective 29/6/2026
 Subject to change or error.