



Skymaster DX - 44842

Probably the only ladder you'll ever need! Our best selling ladder offers unrivalled flexibility and durability.

Product description

- Probably the only ladder you'll ever need! Our best selling ladder offers unrivalled flexibility and durability.
- Upper ladder can also be used separately as single ladders for Order Nos. 44837-44840.
- Sturdy triangular rungs made from extruded profiles that have a horizontal stepping surface when in the use position.
- High-strength Perlon straps with sewn-in fixing tab to prevent splaying.
- Stiles made from extruded aluminium sections for maximum stability.
- Replaceable 2-component plastic end caps ensure positioning without risk of slipping.
- High strength, non-twist rung/stile connections.
- Cannot be used on stairs.



Hints and special features

Complies with EN 131 Professional.

Product features

Coating	Connection between stiles and rungs/stiles	Ladder length as 3-part single ladder	Length as 2-part single ladder and as stepladder with push-	Load capacity
---------	--	---------------------------------------	---	---------------



natural	flanged	8.3 m	on section 5.8 m	max. 150 kg
Material aluminium	Number of rungs 12	Number of rungs 3 × 12	Overall length, retracted 3.54 m	Standards EN 131 professional
Stile depth 85 mm	Transport dimensions 3.550 mm × 500 mm × 220 mm	Tread depth 38 mm	Type of rungs/treads serrated	Vertical distance between each rung/tread 265 mm
Warranty 10 years	Weight 25.9 kg	Wide crosspiece 1.2 m	Working height as 3-part single ladder 9 m	