



Skymaster DX - 44842

Probably the only ladder you'll ever need! Our best selling ladder offers unrivalled flexibility and durability.

Product description

- Probably the only ladder you'll ever need! Our best selling ladder offers unrivalled flexibility and durability.
- Upper ladder can also be used separately as single ladders for Order Nos. 44837-44840.
- Sturdy triangular rungs made from extruded profiles that have a horizontal stepping surface when in the use position.
- High-strength Perlon straps with sewn-in fixing tab to prevent splaying.
- Stiles made from extruded aluminium sections for maximum stability.
- Replaceable 2-component plastic end caps ensure positioning without risk of slipping.
- High strength, non-twist rung/stile connections.
- Cannot be used on stairs.



Hints and special features

Complies with EN 131 Professional.

Product features

| | | | | |
|---------|--|---------------------------------------|---|---------------|
| Coating | Connection between stiles and rungs/stiles | Ladder length as 3-part single ladder | Length as 2-part single ladder and as stepladder with push- | Load capacity |
|---------|--|---------------------------------------|---|---------------|



| | | | | |
|-----------------------|--|---------------------------|---|---|
| natural | flanged | 8.3 m | on section 5.8 m | max. 150 kg |
| Material aluminium | Number of rungs 12 | Number of rungs 3 × 12 | Overall length, retracted 3.54 m | Standards EN 131 professional |
| Stile depth 85 mm | Transport dimensions 3.550 mm × 500 mm × 220 mm | Tread depth 38 mm | Type of rungs/treads serrated | Vertical distance between each rung/tread 265 mm |
| Warranty 10 years | Weight 25.9 kg | Wide crosspiece 1.2 m | Working height as 3-part single ladder 9 m | certification-mark-pf TÜV-SÜD |