



## Skymaster DX - 44844

Probably the only ladder you'll ever need! Our best selling ladder offers unrivalled flexibility and durability.

### Product description

- Probably the only ladder you'll ever need! Our best selling ladder offers unrivalled flexibility and durability.
- Upper ladder can also be used separately as single ladders for Order Nos. 44837-44840.
- Sturdy triangular rungs made from extruded profiles that have a horizontal stepping surface when in the use position.
- High-strength Perlon straps with sewn-in fixing tab to prevent splaying.
- Stiles made from extruded aluminium sections for maximum stability.
- Replaceable 2-component plastic end caps ensure positioning without risk of slipping.
- High strength, non-twist rung/stile connections.
- Cannot be used on stairs.



### Hints and special features

Complies with EN 131 Professional.

### Product features

Certification	TÜV-SÜD
Coating	natural



Connection between stiles and rungs/stiles	flanged
Ladder length as 3-part single ladder	9.45 m
Length as 2-part single ladder and as stepladder with push-on section	6.654 m
Load capacity	max. 150 kg
Material	aluminium
Number of rungs	14
Number of rungs	3 × 14
Overall length, retracted	4.1 m
Standards	EN 131 professional
Stile depth	98 mm
Transport dimensions	4.110 mm × 500 mm × 220 mm
Tread depth	38 mm
Type of rungs/treads	serrated
Vertical distance between each rung/tread	265 mm
Warranty	10 years
Weight	31.5 kg
Wide crosspiece	1.2 m
Working height as 3-part single ladder	10.05 m

ZARGES (U.K.) Ltd.

8 Holdom Avenue, Saxon Park Ind. Est.  
 Bletchley MK1 1QU

Tel: 01908 641118

Fax:  
[sales@zarges.co.uk](mailto:sales@zarges.co.uk)

[www.zarges.com/uk](http://www.zarges.com/uk)

Effective 1/4/2026  
 Subject to change or error.