DATA SHEET

Everest 3DE - 44851

Flexible, safe and inexpensive: the perfect solution for accessing great heights.



PRODUCT DESCRIPTION

- Flexible, safe and inexpensive: the perfect solution for accessing great heights.
- Convenient and precise rung-by-rung height adjustment in increments of 280 mm.
- Upper ladder can be used separately as a single ladder (no. 44851 and 44852).
- Sturdy triangular rungs made from extruded profiles that have a horizontal stepping surface when in the use position.
- Overall width of bottom section: 490 mm.
- Stiles made from extruded aluminium sections for maximum stability.
- Replaceable 2-component plastic end caps ensure positioning without risk of slipping.

HINTS AND SPECIAL FEATURES

Complies with EN 131 Professional.

PRODUCT FEATURES

Property	Value
Coating	natural
Connection between stiles and rungs/stiles	flanged
External width of lower ladder	490 mm

Property	Value
Load capacity	max. 150 kg
Material	aluminium
Number of rungs	8
Number of rungs	3 × 8
Overall length, extended	5.25 m
Overall length, retracted	2.41 m
Standards	EN 131 professional
Stile depth	68 mm
Transport dimensions	2.410 mm × 500 mm × 170 mm
Tread depth	38 mm
Type of rungs/treads	serrated
Vertical distance between each rung/tread	265 mm
Warranty	10 years
Weight	15.3 kg
Wide crosspiece	0.9 m
Working height	5.95 m

ACCESSORIES AND SPARE PARTS

ACCESSORIES 4



Ground spikes
SKU 40939



Stile extension for horizontal stabiliser bars
SKU 41989



Tension strap
SKU 40960



Wall support / base stabiliser
SKU 40250

SPARE PARTS 4



Horizontal stabiliser bar
SKU 800551



Plug-in end cap
SKU 824302



Push-on end cap
SKU 824242



User instructions label
SKU 800604

ZARGES (U.K.) LTD.
Blackwater Trading Estate,
The Causeway
CM9 4LJ Maldon, Essex

Tel: 01908 641118
sales@zarges.co.uk

www.zarges.com/uk
Effective 10/11/2026
Subject to change or error.