



Everest 3DE - 44851

Flexible, safe and inexpensive: the perfect solution for accessing great heights.

Product description

- Flexible, safe and inexpensive: the perfect solution for accessing great heights.
- Convenient and precise rung-by-rung height adjustment in increments of 280 mm.
- Upper ladder can be used separately as a single ladder (no. 44851 and 44852).
- Sturdy triangular rungs made from extruded profiles that have a horizontal stepping surface when in the use position.
- Overall width of bottom section: 490 mm.
- Stiles made from extruded aluminium sections for maximum stability.
- Replaceable 2-component plastic end caps ensure positioning without risk of slipping.



Hints and special features

Complies with EN 131 Professional.

Product features

Coating natural	Connection between stiles and rungs/stiles flanged	External width of lower ladder 490 mm	Load capacity max. 150 kg	Material aluminium
Number of rungs	Number of rungs	Overall length, extended	Overall length, retracted	Standards



8	3 × 8	5.25 m	2.41 m	EN 131 professional
Stile depth 68 mm	Transport dimensions 2.410 mm × 500 mm × 170 mm	Tread depth 38 mm	Type of rungs/treads serrated	Vertical distance between each rung/ tread 265 mm
Warranty 10 years	Weight 15.3 kg	Wide crosspiece 0.9 m	Working height 5.95 m	