



# Everest 3DE - 44851

Flexible, safe and inexpensive: the perfect solution for accessing great heights.

## Product description

- Flexible, safe and inexpensive: the perfect solution for accessing great heights.
- Convenient and precise rung-by-rung height adjustment in increments of 280 mm.
- Upper ladder can be used separately as a single ladder (no. 44851 and 44852).
- Sturdy triangular rungs made from extruded profiles that have a horizontal stepping surface when in the use position.
- Overall width of bottom section: 490 mm.
- Stiles made from extruded aluminium sections for maximum stability.
- Replaceable 2-component plastic end caps ensure positioning without risk of slipping.



## Hints and special features

Complies with EN 131 Professional.

## Product features

Coating <b>natural</b>	Connection between stiles and rungs/stiles <b>flanged</b>	External width of lower ladder <b>490 mm</b>	Load capacity <b>max. 150 kg</b>	Material <b>aluminium</b>
Number of rungs	Number of rungs	Overall length, extended	Overall length, retracted	Standards



<b>8</b>	<b>3 × 8</b>	<b>5.25 m</b>	<b>2.41 m</b>	<b>EN 131 professional</b>
Stile depth <b>68 mm</b>	Transport dimensions <b>2.410 mm × 500 mm × 170 mm</b>	Tread depth <b>38 mm</b>	Type of rungs/treads <b>serrated</b>	Vertical distance between each rung/ tread  <b>265 mm</b>
Warranty <b>10 years</b>	Weight <b>15.3 kg</b>	Wide crosspiece <b>0.9 m</b>	Working height <b>5.95 m</b>	