



## Everest 3DE - 44852

Flexible, safe and inexpensive: the perfect solution for accessing great heights.

### Product description

- Flexible, safe and inexpensive: the perfect solution for accessing great heights.
- Convenient and precise rung-by-rung height adjustment in increments of 280 mm.
- Upper ladder can be used separately as a single ladder (no. 44851 and 44852).
- Sturdy triangular rungs made from extruded profiles that have a horizontal stepping surface when in the use position.
- Overall width of bottom section: 490 mm.
- Stiles made from extruded aluminium sections for maximum stability.
- Replaceable 2-component plastic end caps ensure positioning without risk of slipping.



### Hints and special features

Complies with EN 131 Professional.

### Product features

Coating	natural
Connection between stiles and rungs/stiles	flanged
External width of lower ladder	490 mm
Load capacity	max. 150 kg



Material	aluminium
Number of rungs	10
Number of rungs	3 × 10
Overall length, extended	6.65 m
Overall length, retracted	2.97 m
Standards	EN 131 professional
Stile depth	73 mm
Transport dimensions	2.970 mm × 500 mm × 190 mm
Tread depth	38 mm
Type of rungs/treads	serrated
Vertical distance between each rung/tread	265 mm
Warranty	10 years
Weight	19.2 kg
Wide crosspiece	1.1 m
Working height	7.25 m

ZARGES (U.K.) Ltd.

Blackwater Trading Estate, The Causeway  
 CM9 4LJ Maldon, Essex

Tel: 01908 641118

Fax:  
[sales@zarges.co.uk](mailto:sales@zarges.co.uk)

[www.zarges.com/uk](http://www.zarges.com/uk)

Effective 28/6/2026  
 Subject to change or error.