



Everest 3DE - 44853

Flexible, safe and inexpensive: the perfect solution for accessing great heights.

Product description

- Flexible, safe and inexpensive: the perfect solution for accessing great heights.
- Convenient and precise rung-by-rung height adjustment in a grid of 280 mm.
- Upper ladder can also be used separately as single ladders for Order Nos. 44851-44852.
- Robust extruded-section triangular rungs with step horizontal in working position.
- Overall width of bottom section: 490 mm.
- Stiles made from extruded aluminium sections for maximum stability.
- Replaceable 2-component plastic end caps ensure secure positioning without the risk of slipping.



Hints and special features

Complies with EN 131 Professional.

Product features

| | | | | |
|------------------------------|---|---|--|-----------------------------------|
| Coating natural | Connection Stile-Rung flanged | External width of lower ladder 490 mm | Load capacity max. 150 kg | Material Aluminium |
| Number of rungs 12 | Number of rungs 3 × 12 | Overall length, extended 8.33 m | Overall length, retracted 3.53 m | Pitch rung/tread 265 mm |



| | | | | |
|--------------------------------|----------------|---------------------------------------|----------------|-----------------|
| Standards | Stile depth | Transport dimensions | Tread depth | Type rung/tread |
| EN 131 professional | 85 mm | 3.530 mm × 500 mm × 190 mm | 38 mm | serrated |
| Warranty | Weight | Wide crosspiece | Working height | |
| 10 years | 24.2 kg | 1.2 m | 8.8 m | |