



Everest 3DE - 44853

Flexible, safe and inexpensive: the perfect solution for accessing great heights.

Product description

- Flexible, safe and inexpensive: the perfect solution for accessing great heights.
- Convenient and precise rung-by-rung height adjustment in increments of 280 mm.
- Upper ladder can be used separately as a single ladder (no. 44851 and 44852).
- Sturdy triangular rungs made from extruded profiles that have a horizontal stepping surface when in the use position.
- Overall width of bottom section: 490 mm.
- Stiles made from extruded aluminium sections for maximum stability.
- Replaceable 2-component plastic end caps ensure positioning without risk of slipping.



Hints and special features

Complies with EN 131 Professional.

Product features

Coating natural	Connection between stiles and rungs/stiles flanged	External width of lower ladder 490 mm	Load capacity max. 150 kg	Material aluminium
Number of rungs	Number of rungs	Overall length, extended	Overall length, retracted	Standards



12	3 × 12	8.33 m	3.53 m	EN 131 professional
Stile depth 85 mm	Transport dimensions 3.530 mm × 500 mm × 190 mm	Tread depth 38 mm	Type of rungs/treads serrated	Vertical distance between each rung/ tread 265 mm
Warranty 10 years	Weight 24.2 kg	Wide crosspiece 1.2 m	Working height 8.8 m	