



Everest 3DE - 44854

Flexible, safe and inexpensive: the perfect solution for accessing great heights.

Product description

- Flexible, safe and inexpensive: the perfect solution for accessing great heights.
- Convenient and precise rung-by-rung height adjustment in a grid of 280 mm.
- Upper ladder can also be used separately as single ladders for Order Nos. 44851-44852.
- Robust extruded-section triangular rungs with step horizontal in working position.
- Overall width of bottom section: 490 mm.
- Stiles made from extruded aluminium sections for maximum stability.
- Replaceable 2-component plastic end caps ensure secure positioning without the risk of slipping.



Hints and special features

Complies with EN 131 Professional.

Product features

Coating natural	Connection Stile-Rung flanged	External width of lower ladder 490 mm	Load capacity max. 150 kg	Material Aluminium
Number of rungs 14	Number of rungs 3 × 14	Overall length, extended 9.45 m	Overall length, retracted 4.09 m	Pitch rung/tread 265 mm



Standards	Stile depth	Transport dimensions	Tread depth	Type rung/tread
EN 131 professional	85 mm	4.090 mm × 500 mm × 190 mm	38 mm	serrated
Warranty	Weight	Wide crosspiece	Working height	
10 years	36 kg	1.2 m	9.9 m	