



# Combimaster DX - 44868

The inexpensive alternative for universal use as a extension ladder and stepladder.

## Product description

- The inexpensive alternative for universal use as a extension ladder and stepladder.
- Sturdy triangular rungs made from extruded profiles that have a horizontal stepping surface when in the use position.
- Can be used as a two-section push-up ladder or as a ladder with double-sided access.
- High-strength Perlon straps with sewn-in fixing tab to prevent splaying.
- With cross-tube for stability.
- High strength, non-twist rung/stile connections.
- Stiles and guide fittings of aluminium extruded sections for maximum safety.
- Replaceable 2-component plastic end caps ensure positioning without risk of slipping.



## Hints and special features

Complies with EN 131 Professional.

## Product features

Base	Coating	Connection between stiles and rungs/stiles	Length as trestle	Load capacity
<b>1,64 m × 0,89 m</b>	<b>natural</b>	<b>flanged</b>	<b>2.25 m</b>	<b>max. 150 kg</b>



Material <b>aluminium</b>	Number of rungs <b>8</b>	Number of rungs <b>2 × 8</b>	Overall length, extended <b>3.82 m</b>	Overall length, retracted <b>2.4 m</b>
Standards <b>EN 131 professional</b>	Stile depth <b>58 mm</b>	Transport dimensions <b>2.400 mm × 420 mm × 120 mm</b>	Tread depth <b>38 mm</b>	Type of rungs/treads <b>serrated</b>
Vertical distance between each rung/ tread <b>265 mm</b>	Warranty <b>10 years</b>	Weight <b>10 kg</b>	Wide crosspiece <b>0.89 m</b>	Working height <b>4.9 m</b>