



Combimaster DX - 44868

The inexpensive alternative for universal use as a extension ladder and stepladder.

Product description

- The inexpensive alternative for universal use as a extension ladder and stepladder.
- Sturdy triangular rungs made from extruded profiles that have a horizontal stepping surface when in the use position.
- Can be used as a two-section push-up ladder or as a ladder with double-sided access.
- Anti-spread protection provided by high-strength polyester webbing with a sewn-in attachment tab.
- With cross-tube for stability.
- High strength, non-twist rung/stile connections.
- Stiles and guide fittings of aluminium extruded sections for maximum safety.
- Replaceable 2-component plastic end caps ensure positioning without risk of slipping.



Hints and special features

Complies with EN 131 Professional.

Product features

Base	1,64 m × 0,89 m
Certification	TÜV-SÜD
Coating	natural
Connection between stiles and rungs/stiles	flanged



Length as trestle	2.25 m
Load capacity	max. 150 kg
Material	aluminium
Number of rungs	8
Number of rungs	2 × 8
Overall length, extended	3.82 m
Overall length, retracted	2.4 m
Standards	EN 131 professional
Stile depth	58 mm
Transport dimensions	2.400 mm × 420 mm × 120 mm
Tread depth	38 mm
Type of rungs/treads	serrated
Vertical distance between each rung/tread	265 mm
Warranty	10 years
Weight	10 kg
Wide crosspiece	0.89 m
Working height	4.9 m

ZARGES (U.K.) Ltd.

8 Holdom Avenue, Saxon Park Ind. Est.

Bletchley MK1 1QU

Tel: 01908 641118

Fax:

sales@zarges.co.uk

www.zarges.com/uk

Effective 12/5/2026

Subject to change or error.