



# Combimaster DX - 44870

The inexpensive alternative for universal use as a extension ladder and stepladder.

## Product description

- The inexpensive alternative for universal use as a extension ladder and stepladder.
- Sturdy triangular rungs made from extruded profiles that have a horizontal stepping surface when in the use position.
- Can be used as a two-section push-up ladder or as a ladder with double-sided access.
- High-strength Perlon straps with sewn-in fixing tab to prevent splaying.
- With cross-tube for stability.
- High strength, non-twist rung/stile connections.
- Stiles and guide fittings of aluminium extruded sections for maximum safety.
- Replaceable 2-component plastic end caps ensure positioning without risk of slipping.



## Hints and special features

Complies with EN 131 Professional.

## Product features


Coating <b>natural</b>	Connection between stiles and rungs/stiles <b>flanged</b>	Length as trestle <b>2.81 m</b>	Load capacity <b>max. 150 kg</b>	Material <b>aluminium</b>




**ZARGES**

More information about the product, accessories and spare parts:

<https://www.zarges.com/uk/products/combimaster-dx-44870>



Number of rungs <b>10</b>	Number of rungs <b>2 × 10</b>	Overall length, extended <b>4.94 m</b>	Overall length, retracted <b>2.98 m</b>	Standards <b>EN 131 professional</b>
Stile depth <b>68 mm</b>	Transport dimensions <b>2.970 mm × 430 mm × 120 mm</b>	Tread depth <b>38 mm</b>	Type of rungs/treads <b>serrated</b>	Vertical distance between each rung/tread <b>265 mm</b>
Warranty <b>10 years</b>	Weight <b>12.3 kg</b>	Wide crosspiece <b>0.9 m</b>	Working height <b>5.7 m</b>	 <b>TÜV-SÜD</b>