



Combimaster DX - 44872

The inexpensive alternative for universal use as a extension ladder and stepladder.

Product description

- The inexpensive alternative for universal use as a extension ladder and stepladder.
- Sturdy triangular rungs made from extruded profiles that have a horizontal stepping surface when in the use position.
- Can be used as a two-section push-up ladder or as a ladder with double-sided access.
- Anti-spread protection provided by high-strength polyester webbing with a sewn-in attachment tab.
- With cross-tube for stability.
- High strength, non-twist rung/stile connections.
- Stiles and guide fittings of aluminium extruded sections for maximum safety.
- Replaceable 2-component plastic end caps ensure positioning without risk of slipping.



Hints and special features

Complies with EN 131 Professional.

Product features

Certification	TÜV-SÜD
Coating	natural
Connection between stiles and rungs/stiles	flanged
Length as trestle	3.33 m



Load capacity	max. 150 kg
Material	aluminium
Number of rungs	12
Number of rungs	2 × 12
Overall length, extended	6.06 m
Overall length, retracted	3.54 m
Standards	EN 131 professional
Stile depth	73 mm
Transport dimensions	3.530 mm × 430 mm × 130 mm
Tread depth	38 mm
Type of rungs/treads	serrated
Vertical distance between each rung/tread	265 mm
Warranty	10 years
Weight	15.3 kg
Wide crosspiece	1 m
Working height	6.8 m

ZARGES (U.K.) Ltd.

Blackwater Trading Estate, The Causeway
 CM9 4LJ Maldon, Essex

Tel: 01908 641118

Fax:
sales@zarges.co.uk

www.zarges.com/uk

Effective 26/6/2026
 Subject to change or error.