



Combimaster DX - 44872

The inexpensive alternative for universal use as a extension ladder and stepladder.

Product description

- The inexpensive alternative for universal use as a extension ladder and stepladder.
- Sturdy triangular rungs made from extruded profiles that have a horizontal stepping surface when in the use position.
- Can be used as a two-section push-up ladder or as a ladder with double-sided access.
- High-strength Perlon straps with sewn-in fixing tab to prevent splaying.
- With cross-tube for stability.
- High strength, non-twist rung/stile connections.
- Stiles and guide fittings of aluminium extruded sections for maximum safety.
- Replaceable 2-component plastic end caps ensure positioning without risk of slipping.



Hints and special features

Complies with EN 131 Professional.

Product features

Coating natural	Connection between stiles and rungs/stiles flanged	Length as trestle 3.33 m	Load capacity max. 150 kg	Material aluminium



Number of rungs 12	Number of rungs 2 × 12	Overall length, extended 6.06 m	Overall length, retracted 3.54 m	Standards EN 131 professional
Stile depth 73 mm	Transport dimensions 3.530 mm × 430 mm × 130 mm	Tread depth 38 mm	Type of rungs/treads serrated	Vertical distance between each rung/tread 265 mm
Warranty 10 years	Weight 15.3 kg	Wide crosspiece 1 m	Working height 6.8 m	