



Y-container and SanPack - 45056



Transport and storage container for military applications.

Product description

- Continuously welded shell joints.
- Sturdy 1.5 mm thick sheet metal
- Sturdy base, edge and lid profile.
- Hinged lid with peripheral seal.
- Sturdy cast-iron stacking corners on the lid
- Stacking feet on base with attachment bores inside and outside.
- Waterproof down to the bottom edge of the drop handle thanks to a silicone seal on the inside of the base.
- Equipped with snap fasteners with protection against accidental opening.
- Ergonomic and durable Comfort fasteners that can last at least 20,000 use cycles.
- The lid is removable on B 40.1 Y, B 40.2 Y and B 40Y.
- Rated at IP 54 according to DIN EN 60 529 : 1992

Hints and special features

Clearance dimensions approx. 30 mm less than inside dimensions (length and width). Special sizes on request.

UN approval for the transportation of hazardous goods possible at additional charge.



Product features

Internal dimensions L x W x H	1.175 mm × 793 mm × 465 mm
Max. gross weight dangerous goods permission	137 kg
Outside dimensions max. L x W x H	1.215 mm × 833 mm × 516 mm
Version	B40 Y
Volume	433 l
Weight	22 kg

ZARGES (U.K.) Ltd.

Blackwater Trading Estate, The Causeway
CM9 4LJ Maldon, Essex

Tel: 01908 641118

Fax:
sales@zarges.co.uk

www.zarges.com/uk

Effective 8/6/2026
Subject to change or error.