

Y-container and SanPack - 45058

Transport and storage container for military applications.

Product description


- Continuously welded shell joints.
- Sturdy 1.5 mm thick sheet metal
- Sturdy base, edge and lid profile.
- Hinged lid with peripheral seal.
- Sturdy cast stacking corners on lid and base.
- Stacking feet on base with attachment bores inside and outside.
- The inside edges of the base are sealed with silicone to make the container waterproof up to the lower edge of the drop handle.
- Equipped with snap fasteners with protection against accidental opening.
- Ergonomic and durable Comfort fasteners that can last at least 20,000 use cycles.
- The lid is removable on B 40.1 Y, B 40.2 Y and B 40Y.
- Rated at IP 54 according to DIN EN 60 529 : 1992



Hints and special features

Clearance dimensions approx. 30 mm less than inside dimensions (length and width). Special sizes on request.

UN approval for the transportation of hazardous goods possible at additional charge.



Product features

<p>Internal dimensions L x W x H</p> <p>1.175 mm × 793 mm × 220 mm</p>	<p>Max. gross weight dangerous goods permission</p> <p>75 kg</p>	<p>Outside dimensions max. L x W x H</p> <p>1.215 mm × 833 mm × 270 mm</p>	<p>Version</p> <p>B40.2 Y</p>	<p>Volume</p> <p>205 l</p>
<p>Weight</p> <p>18 kg</p>				