



# Mitraset Classic 19"

## housing - 45810

Enclosure for housing electronic devices in a 19-inch rack

### Product description

- Protection against mechanical stresses such as shocks, impacts, and vibrations. Optional protection against electromagnetic interference.
- IP 65 rated
- Protection against environmental factors such as heat, moisture, moisture, and dust.
- For loads up to 100 kg. Higher loads must be evaluated on a case-by-case basis.
- 3–16 height units (HU), nominal depth (ND) 219–762 mm.
- Housings with nominal depths 219 mm, 350 mm and 480 mm can be stacked together.
- Elastically susp. anti-vibration frame.
- Stacking segments on housing top and bottom.
- Recesses on side walls for drop handles.
- Recess also suitable for accommodating protective pressure compensation valves and humidity indicator.
- Lid with toggle-action snap fasteners.
- ZARGES Comfort Handles for ergonomic handling.
- Fulfils the requirements of VG 95447.
- Tested according to AECTP standards.
- Tested according to MIL-STD-810.
- Significantly better shielding properties compared to plastic enclosures. If necessary, these can be





further improved through special measures.

- Custom modifications are available.
- Made in Germany

## Hints and special features

Also available as UN-approved hazardous goods packaging.

A comprehensive range of special equipment for a wide variety of applications.

## Product features

|                                   |                          |
|-----------------------------------|--------------------------|
| Installation height               | 10 HE/U                  |
| Nominal depth                     | 610 mm                   |
| Outside dimensions max. L x W x H | 704 mm × 534 mm × 526 mm |
| Weight                            | 17.5 kg                  |

ZARGES (U.K.) Ltd.

Blackwater Trading Estate, The Causeway  
CM9 4LJ Maldon, Essex

Tel: 01908 641118

Fax:  
[sales@zarges.co.uk](mailto:sales@zarges.co.uk)

[www.zarges.com/uk](http://www.zarges.com/uk)

Effective 9/6/2026  
Subject to change or error.