
DATA SHEET

# Aluminium shaft covers with trough - 47002

Walkable or drivable shaft covers with choice of surface for indoor and outdoor use.







## PRODUCT DESCRIPTION

- Compliant with DIN EN 124 in conjunction with DIN 1229.
- Tapered profile-section construction with multiple bolted joints.
- Easy to open, no jamming.
- Odour-tight and impervious to surface water.
- Load capacity for shaft cover with cover trough: test force 125 kN (= 12.5 t), only after the cover trough has been filled with B 45 concrete (grain 0-8).
- Incl. lift-out handles (pair) made from stainless steel, comprising one self-lifting opening handle and one lift-out handle.
- Trough depth 60 mm (of which 40 mm covered with construction steel grating and 20 mm free area)

## PRODUCT FEATURES

| Property | Value |
|---|---|
| Design height | 80 mm |
| Inside shaft length | 500 mm |
| Inside shaft size | 500mm × 500mm |
| Inside shaft width | 500 mm |
| Material, cover | aluminium |
| Material, frame | aluminium |

| Property | Value |
| --- | --- |
| Outside dimensions max. L x W x H | 640 mm × 640 mm |
| Transport dimensions | 640 mm × 640 mm × 70 mm |
| Trough depth | 60 mm |

**ZARGES (U.K.) LTD.**
Blackwater Trading Estate,
The Causeway
CM9 4LJ Maldon, Essex

Tel: 01908 641118
sales@zarges.co.uk

www.zarges.com/uk
Effective 11/11/2026
Subject to change or error.