



# Aluminium shaft covers with trough - 47007

Walkable or drivable shaft covers with choice of surface for indoor and outdoor use.

## Product description

- Compliant with DIN EN 124 in conjunction with DIN 1229.
- Tapered profile-section construction with multiple bolted joints.
- Easy to open, no jamming.
- Odour-tight and impervious to surface water.
- Load capacity for shaft cover with cover trough: test force 125 kN (= 12.5 t), only after the cover trough has been filled with B 45 concrete (grain 0-8).
- Incl. lift-out handles (pair) made from stainless steel, comprising one self-lifting opening handle and one lift-out handle.
- Trough depth 60 mm (of which 40 mm covered with construction steel grating and 20 mm free area)



## Product features

Design height	80 mm
Inside shaft length	800 mm
Inside shaft size	800mm × 800mm
Inside shaft width	800 mm
Material, cover	aluminium



Material, frame	aluminium
Outside dimensions max. L x W x H	940 mm x 940 mm
Transport dimensions	940 mm x 940 mm x 70 mm
Trough depth	60 mm

ZARGES (U.K.) Ltd.

Blackwater Trading Estate, The Causeway  
CM9 4LJ Maldon, Essex

Tel: 01908 641118

Fax:  
sales@zarges.co.uk

[www.zarges.com/uk](http://www.zarges.com/uk)

Effective 28/6/2026  
Subject to change or error.