



Combination ladder, 3 sections - 48981

Our base model: lightweight and yet robust.

Product description

- High-quality flange connection between rungs and stiles.
- Stiles made from extruded aluminium sections for maximum stability.
- High-strength polyester webbing with a sewn-in attachment loop – durable and resistant to wear and tear.



Hints and special features

Complies with EN 131 Professional.

Product features

| | |
|---|-------------|
| Coating | natural |
| Connection between stiles and rungs/stiles | flanged |
| Ladder length as 3-part single ladder | 5.12 m |
| Length as 2-part single ladder and as stepladder with push-on section | 3.37 m |
| Load capacity | max. 150 kg |
| Material | aluminium |
| Number of rungs | 8 |
| Number of rungs | 3 × 8 |
| Overall length, retracted | 2.32 m |



Standards EN 131 professional

| | |
|---|--|
| Transport dimensions | approx. 2.318 mm × approx. 460 mm × approx. 180 mm |
| Tread depth | 24 mm |
| Type of rungs/treads | serrated |
| Vertical distance between each rung/tread | 265 mm |
| Warranty | 10 years |
| Weight | 13.3 kg |
| Wide crosspiece | 0.88 m |
| Working height as 3-part single ladder | max. approx. 5.9 m |

ZARGES (U.K.) Ltd.

Blackwater Trading Estate, The Causeway
 CM9 4LJ Maldon, Essex

Tel: 01908 641118

Fax:
 sales@zarges.co.uk

www.zarges.com/uk

Effective 26/6/2026
 Subject to change or error.