DATA SHEET

Combination ladder, 3 sections - 48982

Our base model: lightweight and yet robust.





PRODUCT DESCRIPTION

- High-quality flange connection between rungs and stiles.
- Stiles made from extruded aluminium sections for maximum stability.
- High-strength polyester webbing with a sewn-in attachment loop – durable and resistant to wear and tear.

HINTS AND SPECIAL FEATURES

Complies with EN 131 Professional.

PRODUCT FEATURES

Property	Value
Coating	natural
Connection between stiles and rungs/stiles	flanged
Ladder length as 3-part single ladder	5.96 m
Length as 2-part single ladder and as stepladder with push-on section	3.93 m
Load capacity	max. 150 kg

Property	Value
Material	aluminium
Number of rungs	9
Number of rungs	3 × 9
Overall length, retracted	2.6 m
Standards	EN 131 professional
Transport dimensions	approx. 2.598 mm × approx. 460 mm × approx. 190 mm
Tread depth	24 mm
Type of rungs/treads	serrated
Vertical distance between each rung/tread	265 mm
Warranty	10 years
Weight	14.9 kg
Wide crosspiece	0.99 m
Working height as 3-part single ladder	max. approx. 6.7 m

ZARGES (U.K.) LTD.
Blackwater Trading Estate,
The Causeway
CM9 4LJ Maldon, Essex

Tel: 01908 641118
sales@zarges.co.uk

www.zarges.com/uk
Effective 8/11/2026
Subject to change or error.