



# Combination ladder, 3 sections - 48982

Our base model: lightweight and yet robust.

## Product description

- High-quality flange connection between rungs and stiles.
- Stiles made from extruded aluminium sections for maximum stability.
- High-strength polyester webbing with a sewn-in attachment loop – durable and resistant to wear and tear.



## Hints and special features

Complies with EN 131 Professional.

## Product features

Coating	natural
Connection between stiles and rungs/stiles	flanged
Ladder length as 3-part single ladder	5.96 m
Length as 2-part single ladder and as stepladder with push-on section	3.93 m
Load capacity	max. 150 kg
Material	aluminium
Number of rungs	9
Number of rungs	3 × 9
Overall length, retracted	2.6 m



Standards EN 131 professional

Transport dimensions	approx. 2.598 mm × approx. 460 mm × approx. 190 mm
Tread depth	24 mm
Type of rungs/treads	serrated
Vertical distance between each rung/tread	265 mm
Warranty	10 years
Weight	14.9 kg
Wide crosspiece	0.99 m
Working height as 3-part single ladder	max. approx. 6.7 m

ZARGES (U.K.) Ltd.

8 Holdom Avenue, Saxon Park Ind. Est.  
 Bletchley MK1 1QU

Tel: 01908 641118

Fax:  
[sales@zarges.co.uk](mailto:sales@zarges.co.uk)

[www.zarges.com/uk](http://www.zarges.com/uk)

Effective 12/5/2026  
 Subject to change or error.