



Combination ladder, 3 sections - 48983

Our base model: lightweight and yet robust.

Product description

- High-quality flange connection between rungs and stiles.
- Stiles made from extruded aluminium sections for maximum stability.
- High-strength polyester webbing with a sewn-in attachment loop – durable and resistant to wear and tear.



Hints and special features

Complies with EN 131 Professional.

Product features

Coating	natural
Connection between stiles and rungs/stiles	flanged
Ladder length as 3-part single ladder	6.52 m
Length as 2-part single ladder and as stepladder with push-on section	4.49 m
Load capacity	max. 150 kg
Material	aluminium
Number of rungs	10
Number of rungs	3 × 10
Overall length, retracted	2.88 m



Standards EN 131 professional

Transport dimensions approx. 2.878 mm × approx. 460 mm × approx. 200 mm

Tread depth 24 mm

Type of rungs/treads serrated

Vertical distance between each rung/tread 265 mm

Warranty 10 years

Weight 16.9 kg

Wide crosspiece 0.99 m

Working height as 3-part single ladder max. approx. 7.2 m

ZARGES (U.K.) Ltd.

8 Holdom Avenue, Saxon Park Ind. Est.
Bletchley MK1 1QU

Tel: 01908 641118

Fax:
sales@zarges.co.uk

www.zarges.com/uk

Effective 12/5/2026
Subject to change or error.