



# Combination ladder, 3 sections - 48984

Our base model: lightweight and yet robust.

## Product description

- High-quality flange connection between rungs and stiles.
- Stiles made from extruded aluminium sections for maximum stability.
- High-strength Perlon straps prevent splay.




## Hints and special features

Complies with EN 131 Professional.



## Product features

Coating <b>natural</b>	Connection between stiles and rungs/stiles <b>flanged</b>	Ladder length as 3-part single ladder <b>6.8 m</b>	Length as 2-part single ladder and as stepladder with push-on section <b>4.77 m</b>	Load capacity <b>max. 150 kg</b>
Material <b>aluminium</b>	Number of rungs <b>11</b>	Number of rungs <b>3 × 11</b>	Overall length, retracted <b>3.16 m</b>	Standards <b>EN 131 professional</b>
Transport dimensions <b>approx. 3.158 mm × approx. 460 mm × approx. 220 mm</b>	Tread depth <b>24 mm</b>	Type of rungs/treads <b>serrated</b>	Vertical distance between each rung/tread <b>265 mm</b>	Warranty <b>10 years</b>
Weight <b>20.1 kg</b>	Wide crosspiece <b>1.2 m</b>	Working height as 3-part single ladder		



max. approx. 7.5 m