



Variomaster T - 53794

For quick use and safe standing: folds to compact size and is quickly set up.

Product description

- For quick use and safe standing: folds to compact size and is quickly set up.
- Height can be effortlessly adjusted by just one person due to the self-locking mechanism similar to a push-up ladder.
- Can be easily folded to a compact size for transport and storage.
- Extendable stabilisers with sturdy height-adjustable foot plates for stability and for levelling out on uneven ground.
- Large-area work platform 0.50 x 1.95 m or 0.60 x 2.50 m.
- Peripheral railing for maximum work safety.
- Simple height adjustment according to the self-locking push-up ladder principle, allowing you to reach different heights with only one work platform.
- Operation of height adjustment by one person.
- Easily collapsible for transport and storage.
- Highly mobile and able to pass through doors when erected and collapsed thanks to rollers (Order No. 53794).
- No ballast weights are required for indoor use.
- Two sizes with height adjustment from 1.25 m to 2.46 m or 1.81 m to 3.58 m platform height.
- Scaffolding category 3 (maximum load of 200 kg/m²) according to DIN EN 1004.





Product features

Footpoint, stabiliser rod extended L x W	1,9m × 2,3 m
Footpoint, stabiliser rod retracted L x W	0,8m × 2,3 m
Guardrail height	1 m
Load capacity	max. 195 kg
Overall height	2,31m - 3,52m
Overall height	2.31 m
Platform height	1,25m - 2,46m
Platform length	2.5 m
Platform material	glued plywood panel
Platform width	0.6 m
Transport dimensions	2.290 mm × 780 mm × 750 mm
Tread depth	30 mm
Warranty	10 years
Weight	92 kg
Width, extended	2.3 m
Width, retracted	2.3 m
Working height	4.5 m
closed length	0.8 m
extended length	1.9 m



ZARGES (U.K.) Ltd.

Blackwater Trading Estate, The Causeway
CM9 4LJ Maldon, Essex

Tel: 01908 641118

Fax:
sales@zarges.co.uk

www.zarges.com/uk

Effective 27/6/2026
Subject to change or error.