



# Variomaster T - 53795

For quick use and safe standing: folds to compact size and is quickly set up.

## Product description

- For quick use and safe standing: folds to compact size and is quickly set up.
- Height can be effortlessly adjusted by just one person due to the self-locking mechanism similar to a push-up ladder.
- Can be easily folded to a compact size for transport and storage.
- Extendable stabilisers with sturdy height-adjustable foot plates for stability and for levelling out on uneven ground.
- Large-area work platform 0.50 x 1.95 m or 0.60 x 2.50 m.
- Peripheral railing for maximum work safety.
- Simple height adjustment according to the self-locking push-up ladder principle, allowing you to reach different heights with only one work platform.
- Operation of height adjustment by one person.
- Easily collapsible for transport and storage.
- Highly mobile and able to pass through doors when erected and collapsed thanks to rollers (Order No. 53794).
- No ballast weights are required for indoor use.
- Two sizes with height adjustment from 1.25 m to 2.46 m or 1.81 m to 3.58 m platform height.
- Scaffolding category 3 (maximum load of 200 kg/





**ZARGES**

More information about the product, accessories and spare parts:

<https://www.zarges.com/uk/products/variomaster-t-53795>



$\text{m}^2$ ) according to DIN EN 1004.

## Product features

Footpoint, stabiliser rod extended L x W <b>2,3m × 2,85 m</b>	Footpoint, stabiliser rod retracted L x W <b>1,2m × 2,85 m</b>	Guardrail height <b>1 m</b>	Load capacity <b>max. 300 kg</b>	Overall height <b>2,87m - 4,64m</b>
Overall height <b>2.87 m</b>	Platform height <b>1,81m - 3,58m</b>	Platform length <b>2.5 m</b>	Platform material <b>glued plywood panel</b>	Platform width <b>0.6 m</b>
Transport dimensions <b>2.850 mm × 1.180 mm × 750 mm</b>	Tread depth <b>30 mm</b>	Warranty <b>10 years</b>	Weight <b>119 kg</b>	Width, extended <b>2.85 m</b>
Width, retracted <b>2.85 m</b>	Working height <b>5.6 m</b>	closed length <b>1.2 m</b>	extended length <b>2.3 m</b>	