
DATA SHEET

Multi-section fixed ladder systems, natural alumini - 58638

Multi-section access solution with crossover platform for buildings and machinery.







PRODUCT DESCRIPTION

- For permanent mounting on buildings either for maintenance in accordance with DIN 18 799-1 or as an emergency ladder system in accordance with DIN 14 094-1 or as machine access steps in accordance with DIN EN ISO 14 122-4.
- With safety cage.
- Ladder width: 520 mm.
- Wall brackets with various wall clearances of up to 600 mm can be selected.
- The maximum permissible distance between two wall brackets is 2.00 m. But each ladder section must be mounted with at least two wall brackets.
- Safety barriers, access protection and platforms can be selected to suit individual requirements.
- We can also produce fixed-ladder designs that differ from the standard specification on request.

HINTS AND SPECIAL FEATURES

Dowels and screws/bolts for wall mounting are not included in the scope of delivery.
The prices for double-section systems listed below are calculated as follows: Wall bracket in the form of a U-bar, 200 mm rigid, straight stile extensions on both sides, crossover platform, incl. back cage in accordance with DIN 18 799-1.In the case of other requirements, please use our planning system for fixed ladders.

PRODUCT FEATURES

Property	Value
Material	Natural aluminium

Property	Value
Overall length incl. stile	14.9 m
Warranty	10 years
access height	13.8 m

ZARGES (U.K.) LTD.
Blackwater Trading Estate,
The Causeway
CM9 4LJ Maldon, Essex

Tel: 01908 641118
sales@zarges.co.uk

www.zarges.com/uk
Effective 10/11/2026
Subject to change or error.