DATA SHEET

Skymaster EFAmix X - GRP41521

The Skymaster is strong, sturdy and safely insulated thanks to glass reinforced polyester (GRP) stiles, making it ideal for working with electrical equipment or near electrical hazards.



PRODUCT DESCRIPTION

- The Skymaster is strong, sturdy and safely insulated thanks to glass reinforced polyester (GRP) stiles, making it ideal for working with electrical equipment or near electrical hazards.
- High level of protection provided for working on electrical installations thanks to insulated stiles made from glass-fire-reinforced plastic.
- One rigid locking bar.
- Aluminium rungs (30 x 30 mm).
- Anti-spread protection provided by high-strength polyester webbing with a sewn-in attachment tab.
- Optimum wrap-around stile guide that encompasses the whole rung.
- Locks safely by means of rung hooks and locking tab.
- Replaceable 2-component plastic end caps ensure positioning without risk of slipping and at the same time provide firm seating in the stile.

HINTS AND SPECIAL FEATURES

Complies with EN 131 Professional.

PRODUCT FEATURES

Property	Value
Certification	TÜV-SÜD

Property	Value
Connection between stiles and rungs/stiles	flanged
Ladder length as 3-part single ladder	5.8 m
Length as 2-part single ladder and as stepladder with push-on section	4.1 m
Load capacity	max. 150 kg
Material	Aluminium / plastic
Number of rungs	8
Number of rungs	3 × 8
Overall length, retracted	2.45 m
Standards	EN 131 professional
Stile depth	73 mm
Tread depth	30 mm
Type of rungs/treads	serrated
Vertical distance between each rung/tread	265 mm
Warranty	10 years
Wide crosspiece	1 m
Working height as 3-part single ladder	6.55 m

ACCESSORIES AND SPARE PARTS

SPARE PARTS 1



User instructions label
SKU 800605

ZARGES (U.K.) LTD.
Blackwater Trading Estate,
The Causeway
CM9 4LJ Maldon, Essex

Tel: 01908 641118
sales@zarges.co.uk

www.zarges.com/uk
Effective 9/11/2026
Subject to change or error.