



# K 424 XC Mobile Box

The new K 424 XC combines the legendary quality of ZARGES cases with new mobility.

## **Product description**

- The K 424 XC has excellent mobility and ergonomics owing to its integrated wheels and pull-out handles (for order no. 41810-41814) or second sprung drop handle on the end face (for order no. 41815).
- All-round beading and corner beading offer additional stability, allowing the box to withstand a load of up to 50 kg despite its low weight.
- Can be stacked securely thanks to stacking corners made of impact-resistant plastic and integrated stacking elements in the support frame. Also stackable with ZARGES K 470 boxes and Euroboxes.
- Can be fitted with an optional 125 mm wheel set or 220 mm off-road wheel set (for models with a volume of 60 litres and above) to improve its mobility on difficult terrain.
- Sturdy, mobile aluminium box with long service life.
- Optimum mobility through integrated 50 mm wheels and pull-out handle (order no. 41810-41814) or second sprung drop handle on the end face (order no. 41815).
- Extremely smooth-running due to special castors, ø
   50 mm, made from polyurethane and polyamide.
- ZARGES Comfort fasteners with extremely long service life, fitted with plug locks.
- High load-bearing capacity of up to 50 kg despite













the low dead weight.

- UN approval for the transportation of hazardous goods possible at additional charge.
- Optional 125 mm wheel set or 220 mm off-road wheel set (for models with a volume of 60 litres and above) available for use in difficult terrain.
- All-round beading and corner beads for additional dimensional stability.
- A wide range of adjustable interior fittings ensure versatility.
- Lid equipped with peripheral foamed seal for protection against dust and splash water.

## Hints and special features

Clearance dimensions approx. 30 mm less than inside dimensions (length and width). Special sizes on request.

#### **Product features**

Colour of the stacking corners  Natural aluminium	Fasteners  Comfort fasteners	Handles  Sprung drop handles	Integrated wheels Yes	Material aluminium
Material of the stacking corners  aluminium	Seal foamed lid seal	Stacking corners Yes	Wheel diameter 50 mm	

#### **Product variants**

SKU	SKU	SKU

Tel: 01908 641118

www.zarges.com/uk sales@zarges.co.uk





41810	41811	41812
Corner beading  No	Corner beading Yes	Corner beading Yes
Internal dimensions L x W x H  516 mm × 350 mm × 159 mm	Internal dimensions L x W x H  550 mm × 350 mm × 310 mm	Internal dimensions L x W x H  750 mm × 350 mm × 380 mm
Max. gross weight dangerous goods permission  25 kg	Max. gross weight dangerous goods permission  25 kg	Max. gross weight dangerous goods permission  35 kg
Outside dimensions max. L x W x H  550 mm × 400 mm × 233 mm	Outside dimensions max. L x W x H  600 mm × 400 mm × 385 mm	Outside dimensions max. L x W x H  800 mm × 400 mm × 455 mm
Peripheral beading  No	Peripheral beading Yes	Peripheral beading Yes
Pull handle  3-section	Pull handle  3-section	Pull handle 2-section
Total max. weight 25 kg	Total max. weight 25 kg	Total max. weight  35 kg
Volume 28 l	Volume 60 l	Volume 99 l
Weight 6.3 kg	Weight 7.3 kg	Weight  9 kg
SKU 41813	SKU 41814	SKU 41815
Corner beading Yes	Corner beading Yes	Corner beading Yes
Internal dimensions L x W x H	Internal dimensions L x W x H	Internal dimensions L x W x H





750 mm × 450 mm × 310 mm	750 mm × 635 mm × 410 mm	910 mm × 350 mm × 380 mm
Max. gross weight dangerous goods permission	Max. gross weight dangerous goods permission	Max. gross weight dangerous goods permission
35 kg	35 kg	50 kg
Outside dimensions max. L x W x H	Outside dimensions max. L x W x H	Outside dimensions max. L x W x H
800 mm × 500 mm × 385 mm	800 mm × 685 mm × 485 mm	960 mm × 400 mm × 455 mm
Peripheral beading	Peripheral beading	Peripheral beading
Yes	Yes	Yes
Pull handle	Pull handle	Pull handle
2-section	2-section	2. Sprung drop handle
Total max. weight	Total max. weight	Total max. weight
35 kg	35 kg	50 kg
Volume	Volume	Volume
105 l	195 l	120 l
Weight	Weight	Weight
9.5 kg	12 kg	9.5 kg